

SURFACE RESISTANCE TESTER CODE 0740-SU13

DATA
OUTPUT



- Designed to EOS/ESD, CECC, ASTM and UL standards.
- Suitable for testing table mats, floors, paint, work clothes, bags, etc.
- Automatic selection of resistance range and test voltage

SPECIFICATION

| | |
|---------------------|--|
| Range | $1 \times 10^3 \sim 1 \times 10^{13} \Omega$ |
| Accuracy | $< 10^{11}$: 10% $\geq 10^{11}$: 20% |
| Test voltage | 10V/100V, $\pm 5\%$ |
| Test time | 15s, 30s, 60s |
| Working environment | temperature: $0^\circ\text{C} \sim 49^\circ\text{C}$, humidity: $\leq 80\%$ |
| Power supply | rechargeable lithium battery: 3.7V, 1800mAh |
| Dimension (W×D×H) | 115×79×69mm |
| Weight | 630g |

STANDARD DELIVERY

| | |
|-------------------|-------|
| Main unit | 1 pc |
| Electrode | 2 pcs |
| Conductive rubber | 2 pcs |
| Test lead | 3 pcs |
| Test rack | 1 pc |
| Power adapter | 1 pc |

OPTIONAL ACCESSORY

| | |
|--------------------------|-----------|
| Digital thermohygrometer | 9362-TH27 |
| Digital thermohygrometer | 0317-TH37 |